



experience,
trust, service

800-BLAST-IT
www.marcousa.com

Dallas, TX • Davenport, IA • Harrisburg, PA • Houston, TX • New Orleans, LA • Savannah, GA

Autofax #00093705
page 1 of 2

Updated: 02/26/07

MSDS SHEET - COAL SLAG - LAWRENCEBURG, IN

I. Product Identification

Trade Name as Labeled: Coal Slag, Black Lightning
Chemical Name and Formula: Coal Slag
Plant Location: Tanner's Creek
P.O. Box 253
Lawrenceburg, IN 47025
Emergency & Information Telephone #: 800-252-7848

II. Hazardous Ingredients

Iron Oxide: 1-60%
Amorphous Silica: 1-55%
Crystalline Silica: < 1%
Titanium Dioxide: 0-5%
Magnesium Oxide: 0-6%
Potassium Oxide: 0-5%
Sulfur Trioxide: 0-15%
Phosphorus Pentoxide: 0-1%
Aluminum Oxide: 15-40%
Calcium Oxide: 0-30%
Sodium Oxide: 0-2%

NOTE: The PEL and the TLV for this component do not currently exist.

III. Physical Properties

Vapor Density: N/A
Boiling Point: N/A
Evaporation Rate: N/A
Specific Gravity: 2-3
Solubility in Water: Moderate
Vapor Pressure: N/A

Fly Ash: Consists primarily of minute, separate glass spheres with crystalline matter and varying amounts of unburned carbon. Glass spheres range in size from approximately .007 mm (medium silt) to .2 mm (fine sand) or 7 to 20 microns. Colors range from light tan or light gray to almost black depending on the proportions of carbon and iron.

Bottom Ash: Consists of a granular material with similar upper and lower particle size limits to fine concrete aggregate (concrete sand). Basic particle shape is angular. Colors range from a medium brown or medium gray to almost black.

Boiler Slag: Consists of a granular material. Basic particle shape is angular. Color is consistently shiny and black resembling crushed coal or black glass.

IV. Fire & Explosion

Flammable: No
Unusual Fire Hazards: N/A
Flammable Limits: N/A
Extinguishing Media: N/A
Explosive: No
Unusual Explosion Hazards: N/A
Flash Point: N/A
Special Fire Fighting Procedures: N/A

V. Health Hazard Information

Symptoms of Overexposure:
Inhaled: Irritation to the respiratory tract. Immediately remove affected person to fresh air from source. If unusual coughing, tightness in chest, or shortness of breath occurs after exposure, immediately contact physician or medical personnel.
Contact with Eyes or Skin: Irritation to skin and eyes. For eyes: flush thoroughly with water. For skin: wash skin with soap and water if irritation occurs.
Swallowed: Rinse mouth out with water
First Aid: Emergency procedures

MSDS SHEET - COAL SLAG - LAWRENCEBURG, IN

VI. Reactivity Data

Stability: Stable
Hazardous Polymerization: None

Incompatibility (Materials to Avoid): None
Hazardous Decomposition Products: None

VII. Spill, Leak and Disposal Procedures

Spill Response Procedures (including employee protection measures): Clean up using water and other methods to reduce airborne dust.

Waste Disposal: Material may be disposed of as an inert solid in an appropriate solid waste landfill. See applicable Federal, State, and Local Regulations.

VIII. Special Handling Information

Ventilation and Engineering Controls: Use in unconfined areas with adequate ventilation.

Respiratory Protection (Type): Use NIOSH or MSHA approved respirators. If you are unsure as to the type of respirator to be used, please consult your employer.

Eye Protection (Type): Safety glasses or goggles.

Gloves (Specify Material): Use safety gloves to avoid skin irritation.

Other Protective Clothing & Equipment: Wear appropriate personal protective equipment.

Work Practices, Hygienic Practices: Clean up spills promptly. Do not engage in activities that will generate airborne dust particles.

Other Handling & Storage Requirements: Avoid generating dust. No special storage requirements. Train all exposed persons in all sections of this MSDS and the proper handling of coal slag before they work with this product.

See OSHA Hazard Communication Rule CRF 1910.1200, 1915.99, 1917.28, and 1928.21, state, local worker, or community "Right to Know" laws and regulations. We recommend that smoking be prohibited in all areas where respirators must be used. Warn your employees (and your customers in case of resale) by posting and other means of the hazard and OSHA precautions to be used. Provide training about the OSHA precautions.

IX. Silicosis Warning

▲ DANGER Breathing dust containing silica will cause silicosis, a fatal lung disease. Breathing dust during blasting operations will cause asbestosis, lead poisoning and/or other serious or fatal diseases. A NIOSH-approved, well-maintained, supplied-air abrasive blasting respirator must be used by anyone blasting, anyone handling or using the abrasive and anyone in the area of the dust. Harmful dust containing toxic material from abrasives or surfaces being blasted can remain suspended in the air for long periods of time after blasting has ceased. Failure to avoid the above danger will result in death or serious injury.

▲ DANGER You must comply with all OSHA, local, City, State, Province, Country and jurisdiction regulations, ordinances and standards, related to your particular work area and environment. Keep unprotected individuals out of the work area. Failure to avoid the above danger will result in death or serious injury.

DISCLAIMER: The information in this MSDS was obtained from sources, which we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding accuracy. These conditions or methods of handling, storage use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Customers/users of silica must comply with all applicable health and safety laws, regulations and orders, including the OSHA Hazardous Communication Standard.



For more information call:

800-BLAST-IT

Phone: 800-252-7848

Fax: 563-324-6258

e-mail: sales@marcouisa.com

www.marcouisa.com

